

# SiViB Record Display



## Display for Vibration and Bearing Monitor SiViB Record

- **Overview Table of all values**
- **Bargraph for single channels**
- **Panel mounting**
- **RS232 or CAN-Bus connection**

SiViB Record Display is to be used for displaying measurement values acquired by a SiViB Record 1500 series monitor. The backlit LCD with 4 rows of 20 characters has a good readability, even from some distance.

The display has 3 operation modes:

1. Overview, numerical display of all values in a table
2. Bargraph and numerical display for one single channel
3. Bargraph and numerical display for one channel, automatic switching through all channels.

## Connection to the SiViB Record Monitor via RS232 or CAN-Bus



## Overview

All values in one screen as digital numbers



## Bargraph

Bargraph and numerical values for one measurement channel

## SiViB Record Display

### Specifications

Display	LCD monochrome with backlight 4 rows with 20 characters each
Case	„Through hole“ front panel mounting W 144 x H 72 x D 64 mm (Without connectors) Cutout 138 x 68 mm
Display modes:	Mode Overview: Values of 6 units plus RPM as numbers, digital inputs as 0 or 1  Mode Bargraph: 2 values from 1 input channel as number and block bargraph, fixed channel selection; RPM as number  Modus Changing Display: same as Bargraph, but automatically scanning through the channels in 10 sec. Interval
Operation Keys	Up, Down, Enter; needed for configuration only
Inputs / Outputs:	Power supply: 24 VDC; approx. 170 mA; Combicon connector RS232C port: 9-pin sub D male; for Null-Modem-Cable to SiViB Record CAN-Bus: 2-pin Combicon connector



Backside view

### Models and Order Numbers:

Model	Description	Order Number
SiViB Record Display	Values Display for SiViB Record	SiV09.902

#### IBIS GmbH

Werner-von-Siemens-Str. 21  
64319 Pfungstadt

**Tel:** (0)6157-949-370  
**Fax:** (0)6157-949-100

**www.ibis-gmbh.de**  
**info@ibis-gmbh.de**